


► INFLATABLES

	AEROTEC 380
DIMENSIONS (METERS - FEET/INCHES)	
Overall length	3,8 - 12'6"
Inside length	2,5 - 8'2"
Overall width	1,65 - 5'5"
Inside width	0,74 - 2'5"
Buoyancy tube diameter	0,455 - 1'6"
CAPACITY	
Passengers (ISO)	5
Maximum payload (kg - lbs)	690 - 1521,2
Total weight ¹ (kg - lbs)	43 - 94,8
Airtight compartments	3+2
DESIGN CATEGORY²	
European directive N° 94/25/CE	C
MOTORISATION	
Shaft: ● Short ■ long ✖ Extralong * Ultralong ▲ Jet	●
Average recommended power (in HP)	15
Average recommended power (in kW)	12
Maximum power allowed (Hp)	25
Maximum power allowed (kW)	19
Maximum weight of outboard ³ (kg - lbs)	72 - 158,7
Maximum speed (km/h - mph)	43 - 27
DIMENSIONS OF THE FOLDED BOAT (METERS - FEET/INCHES)	
Length of 1st bag	1,15 - 3'9"
Width of 1st bag	0,72 - 2'4"
Height of 1st bag	0,39 - 1'3"
Length of 2nd bag	-
Width of 2nd bag	-
Height of 2nd bag	-

(1) The weights indicated for the Typhoon, AX, MAX, AX Compact and MAX RIB include the floorboard, paddles/oars and pump.

(2) Applies only for EEC (European directive 94/25/CE).

(3) Maximum authorized weight: Dry weight, according to the engine manufacturers catalogue's specifications.



EQUIPMENT LIST			
HULL	BUOYANCY TUBE	STANDARD EQUIPMENT	OPTIONAL EQUIPMENT
<ul style="list-style-type: none"> • Removable V-shaped hull made up of two inflatable sections • Aluminium motor plate • Attachment points for launching wheels • Self-bailer 	<ul style="list-style-type: none"> • 1100 Decitex fabric • Semi-recessed valves • Safety flex handrails • Spray deflecting large-profile rubbing strake • 2 towing rings • 2 carrying handles • 1 metal bow handle 	<ul style="list-style-type: none"> • 2 paddles • 1 bench seat • 1 removable bow bag • 1 carry bag with utility pockets • 1 high pressure pump • 1 repair kit • Owner's manual • 1 pressure gauge 	<ul style="list-style-type: none"> • Launching wheels • Fishing rod holder • Overall cover • Crossbar steering kit • Boarding ladder • Trolley • Electric pump